

XRS series

18-20V X-RAY GENERATORS

Have you checked the
PULSE
of the industry?



Pulsed X-ray Advantages

Penetrating power in a small container

Utilitarian design - DeWalt battery, tripod mounts, picatinny rail, removable top plate

Lightweight - less than 20 lbs

Safety - no radioactive material, minimal leakage, short exposure time

Easy to use - One input variable

	XRS3	XRS4
Dimensions (with battery)	L: 15.42" (39.17 cm)	L: 19.26" (48.92 cm)
(with Picatinny Rails)	W: 4.26" (10.82 cm)	W: 4.80" (12.19 cm)
(without key)	H: 5.83" (14.81 cm)	H: 7.05" (17.91 cm)
Weight (with battery)	11.80 lbs. (5.40 kg)	18.30 lbs (8.30 kg)
Average Output Dose*	3 mR per pulse	6.25 mR per pulse
Pulse Rate	21 pulses per second	9 pulses per second
Pulses per Battery charge	5500	3000
Minimum Standby Time	10 hours	10 hours
IP Rating	IP 54	IP 54
LCD	80 Character	80 Character
Duty Cycle	200 pulses 4 minutes	200 pulses 4 minutes

*Dose measured at 12" (30 cm) from source

 **Golden Engineering**
Portable X-ray Technology

WEB: www.goldenengineering.com

PH: 765-855-3493

EM: sales@goldenengineering.com